

# PRODUCT DATASHEET

## P LINE 118.0 mm 150 17.5 W/2700K R7s

PARATHOM LINE R7s | Double-ended special LED lamps



---

### AREAS OF APPLICATION

- Hospitality
- Domestic applications
- Outdoor applications only in suitable luminaires

---

### PRODUCT BENEFITS

- Long lifetime of up to 15,000 h
- Low energy consumption
- Four year guarantee
- Good all-around light emission
- Fits into most R7s luminaires thanks to excentric base

---

### PRODUCT FEATURES

- LED alternative to conventional R7s lamps



**TECHNICAL DATA**

Electrical data

Rated wattage	17.50 W
Nominal wattage	17.50 W
Nominal voltage	220...240 V
Max. lamp no. on circuit break. 10 A (B)	22
Max. lamp no. on circuit break. 16 A (B)	35
Operating frequency	50/60 Hz
Power factor $\lambda$	0.50
Claimed equiv. conventional lamp power	150 W

Photometrical data

Nominal luminous flux	2452 lm
Rated luminous flux	2452 lm
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Warm White
Color temperature	2700 K
Luminous flux	2452 lm
Color rendering index Ra	$\geq 80$
Standard deviation of color matching	$\leq 6$ sdc <sub>m</sub>
Rated color temperature	2700 K
Color rendering index Ra	$\geq 80$

Light technical data

Warm-up time (60 %)	< 0.50 s
Beam angle	360.00 °
Starting time	< 0.5 s

Dimensions & weight



<b>Overall length</b>	118.0 mm
<b>Diameter</b>	28.0 mm
<b>Outer bulb</b>	-
<b>Length</b>	118.0 mm

#### Temperatures & operating conditions

<b>Ambient temperature range</b>	-20...+40 °C
<b>Maximum temperature at tc test point</b>	103 °C

#### Lifespan

<b>Nominal lamp life time</b>	15000 h
<b>Rated lamp life time</b>	15000 h
<b>Number of switching cycles</b>	100000
<b>Lumen maintenance at end of service life</b>	0.70

#### Additional product data

<b>Base (standard designation)</b>	R7s
<b>Mercury content</b>	0.0 mg
<b>Show WEEE picto</b>	Yes

#### Capabilities

<b>Dimmable</b>	No
-----------------	----

#### Certificates & standards

<b>Energy efficiency class</b>	A++
<b>Energy consumption</b>	18 kWh/1000h

#### Country-specific categorizations

<b>Order reference</b>	LEDPLI118150 17
------------------------	-----------------

#### SAFETY ADVICE

To ensure full light efficiency and product lifetime, it is recommended to detach any glass or cover of the luminaire.

#### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075168992	Folding carton box 1	30 mm x 30 mm x 122 mm	117.00 g	0.11 dm <sup>3</sup>
4058075169005	Shipping carton box 20	159 mm x 129 mm x 131 mm	2394.00 g	2.69 dm <sup>3</sup>

---

4058075169012	Shipping carton box 120	269 mm x 169 mm x 411 mm	14562.00 g	18.68 dm <sup>3</sup>
---------------	----------------------------	--------------------------	------------	-----------------------

---

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

#### REFERENCES / LINKS

For further products and actual information concerning LED lamps see

▶ [www.ledvance.com/ledlamps](http://www.ledvance.com/ledlamps)

For Guarantee see

▶ [www.ledvance.com/guarantee](http://www.ledvance.com/guarantee)

---

#### DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.